



THERRIEN TS1 & TS1-HV

LEAF & DEBRIS BLOWER



TS1

11,000 CFM
214 MPH WIND SPEED
NOISE LEVEL 80 DB

TS1-HV (HIGH VOLUME)

14,300 CFM
273 MPH WIND SPEED
NOISE LEVEL 82 DB

TS1 & TS1-HV LEAF & DEBRIS BLOWER

Therrien Leaf & Debris Blowers generate more air with less noise. Precision manufacturing increases air flow and reduces the noise typically associated with 3-point hitch blowers.

	TS1	TS1-HV
Impeller Speed	<ul style="list-style-type: none"> • 1288 RPM at a PTO speed of 540 RPM. 	<ul style="list-style-type: none"> • 1674 RPM at a PTO speed of 540 RPM.
Air-Flow	<ul style="list-style-type: none"> • Minimum 11,000 CFM • 214 MPH Wind Speed 	<ul style="list-style-type: none"> • Minimum 14,300 CFM, The highest in it's class. • 273 MPH Wind Speed
Tractor	<ul style="list-style-type: none"> • Minimum 25 PTO HP recommended. • PTO: 540 RPM • Three point hitch: Cat 1 	<ul style="list-style-type: none"> • Minimum 40 PTO HP recommended. • PTO: 540 RPM • Three point hitch: Cat 1
Fan	<ul style="list-style-type: none"> • 8 Bladed fan, 36" in diameter. • Housing: 3/16" Plate Steel 	
Drive	<ul style="list-style-type: none"> • Belt & Pulley: PTO Driven. • Powerband band belt with constant tensioning for easy maintenance and improves performance. 	
General	<ul style="list-style-type: none"> • Turf Protection: Rounded base with full width anti-scuff rear roller. • Castor Wheels (2): Adjustable from 0 - 1.5" in .5" increments. 4.1 X 3.5-6, 6-ply, 50 PSI. • Weight: 880 lbs • Lift Ring: Standard. • PTO Shaft: Included • Dimensions: L-37" H-53" W-44" (without optional air-flow chute) • Options: Directional Air-Flow Chute - Redirects air flow 180 degrees. • Saety Grill- Sheild discharge opening 	
Warranty	One year limited warranty	

Therrien & fils inc.

380, Principale
St-Nazaire, Qc, Canada
J0H 1V0

Tel.: 819 392-2846
Fax.: 819 392-2888
Email: atherrien@cooptel.qc.ca

www.atherrien.com

