



VAC 200 & VAC 220

SWEeper VACS



7.1 AND 10 CUBIC YARDS CAPACITY

84" PICKUP HEAD



OPTIONAL SUCTION HOSE

VAC 200 & 220 SWEEPER VACS

FOR YOUR TOUGHEST CLEAN-UP JOBS.

Therrien Vacs combines a rubber finger pick-up unit with a high volume & velocity vacuum system to efficiently remove leaves and debris from fine turf areas. They are built tough with stainless steel lined impeller housings, rectangular tube steel construction and hydraulically dumped galvanized steel hoppers.



Automatic Opening Rear Door



	VAC 200	VAC 220
Hopper	<ul style="list-style-type: none"> Capacity: 7.1 Cubic yards (72" X 48" X 96") 	<ul style="list-style-type: none"> Capacity: 10 Cubic yards (72" X 54" X 120")
Pick-up Unit	<ul style="list-style-type: none"> Construction: Galvanized steel to resist corrosion. Tapered Sides: Allows debris to load without compressing against the hopper walls for clean dumping. Dump System: Hydraulic dump with automatic opening rear door. Unique shape helps boxdump cleanly; Horizontal duct dumps with box to prevent clogging. Sight window allows operator to monitor load. 	
Impeller	<ul style="list-style-type: none"> General: 84" Pick-up width with 4 rows of sweeping fingers (130 total). Anti-scalp turf rollers. Sweeping Fingers: Steel braided to resist wear. Height System: Infinitely adjustable with 2 - 6" wheels. Access Panels: (4) Removable panels for easy access and cleaning. Drive System: Hydraulic with quick couplers for easy disconnecting. Lift/Lower: Rotating hydraulic system gently lifts the pick-up unit for easy transportation. 	
Impeller Housing	<ul style="list-style-type: none"> Construction: 3/8" steel, 35" diameter, PTO driven (540 RPM). Blades: Curved to improve efficiency and wear characteristics. Blade Reinforcement: Robust gussets to add strength. Lined with stainless steel coating to increase Rockwell. 	
Impeller Housing	<ul style="list-style-type: none"> Lining: Stainless steel, increases Rockwell hardness from 18 to 84. Accessibility/ Clean Out: Easy access from the top for cleaning. Fitted with an oversized drain plug. 	
Controls	Pick-up unit -- lift/lower. Pick-up unit -- on/off. Dump box -- raise/lower.	
General	<ul style="list-style-type: none"> Weight: Vac 200 - 3560 lbs Dimensions: L-192" X H-85" X W-88" 	<ul style="list-style-type: none"> Weight : 4060 lbs Dimensions: L-216" X H-85" X W-88"
Suction Hose (optional)	<ul style="list-style-type: none"> Impeller Drive: 3 belts. Noise Level: 91 DBA. Hitch/Jack Stand: Pin hitch with variable heights for different tractors. Remote storage point for jack stand and PTO. Grease Points: Easily accessible, clearly marked. Tractor Requirements: 5 GPM double plug-in hydraulics and 30 PTO H.P. minimum. Tongue: Adjustable for proper sweeper angle. Dust control cover: Deflects dust away from the operator Clevis: Adjustable to fit all tractor drawbars 	
Warranty	One year limited warranty	

Therrien & fils inc.

380, Principale
St-Nazaire, Qc, Canada
J0H 1V0

Tel.: 819 392-2846
Fax.: 819 392-2888
Email: atherrien@cooptel.qc.ca

www.atherrien.com

